



a.b.e.[®] Construction Chemicals **carbolineum**

COAL TAR WOOD PRESERVATIVE

DESCRIPTION

carbolineum is a dark brown to black liquid derived entirely from coal tar and having a typical coal tar odour. It is a blend of **creosote** and coal tar.

USES

It is intended for use in the preservation of timber, exterior use only. The toxicity and strong odour prohibit the interior use of **carbolineum** for both human and animal habitation. It should not come into contact with food or potable water.

FEATURES & BENEFITS

- Protection of wooden poles, wooden fences eaves and rafters.
- Economical wood preservative.
- Easy to apply.

SURFACE PREPARATION

All surfaces to be clean, dry and sound.

BONDING / PRIMING

No primer required.

MIXING

Stir well before and during use.

COVERAGE

2 - 6 m² / l

APPLICATION

Application by brush or dip.

CLEANING

Tools, brushes and mixing equipment should be cleaned immediately after use and before material has set with **abe[®] super brush cleaner** followed by washing with soap and water.

TYPICAL PHYSICAL PROPERTIES

Active ingredients	creosote 70% by volume
Consistency	Thin liquid
Toxicity	Toxic
Flash point	95°C minimum
Fire resistance	Flammable liquid

PROTECTION ON COMPLETION

None

TEMPERATURE AND RELATIVE HUMIDITY

Do not apply if temperature is below 5°C.

MODEL SPECIFICATION

Coal tar based wood preservative. The wood preservative will be **carbolineum**, a **creosote**/coal tar blend wood preservative applied in accordance with the recommendations of **a.b.e.[®] Construction Chemicals**.

PACKAGING

5 l, 25 l and 200 l containers.

HANDLING & STORAGE

This product has a shelf life of 12 months if kept in a dry cool place in the original packaging. In more extreme conditions this period might be shortened.

HEALTH & SAFETY

All tar-based products are classed as carcinogenic. **carbolineum** is toxic and flammable. Always ventilate a working area very well during application in order to remove fumes. The fumes are extremely strong smelling and the smell lingers for a long time. Avoid naked flames in the vicinity. Avoid excessive inhalation and skin contact. Clean hands well before smoking or eating. If material is splashed into the eye, wash well with plenty of clean water and seek medical attention.

Note: Never store treated articles in the vicinity of fish, birds, bees or animals.

IMPORTANT NOTE

This data sheet is issued as a guide to the use of the product(s) concerned. Whilst **a.b.e.® Construction Chemicals** endeavours to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot - because **a.b.e.®** has no direct or continuous control over where and how **a.b.e.®** products are applied - accept any liability either directly or indirectly arising from the use of **a.b.e.®** products, whether or not in accordance with any advice, specification, recommendation, or information given by the company.

FURTHER INFORMATION

Where other products are to be used in conjunction with this material, the relevant technical data sheets should be consulted to determine total requirements. **a.b.e.® Construction Chemicals** has a wealth of technical and practical experience built up over years in the company's pursuit of excellence in building and construction technology.



a.b.e.® is an ISO 9001:2008 registered company
PO Box 5100, Boksburg North, 1461, South Africa
Website: www.abe.co.za | Tel: +27(0) 11 306 9000
Durban | Johannesburg | Cape Town | Port Elizabeth | East London | Bloemfontein | George

a.b.e.® is a Chryso Group Company

CHRYSO
CHEMICAL SOLUTIONS FOR THE
CONSTRUCTION MATERIALS INDUSTRY
DATE UPDATED: 08/11/13