

PRODUCT DATA SHEET

Bit-U-Tape

Self-Adhesive Waterproofing Tape

Product Description:

SCC Bit-U-Tape is a bitumen aluminium self-adhesive waterproofing tape.

Characteristics/Advantages:

- Easy to use
- Self-adhesive/ Peel and stick
- Extremely tough and flexible

Uses:

SCC Bit-U-Tape is suitable for sealing or repairing galvanised roof sheeting with leaks, holes, roof sheeting, overlaps, down pipes, valley gutters, roof screws, pipe vents, ridging and capping.

Product Properties:

Physical Form:	Bitumen aluminium tape
Colour:	Silver
Thickness of aluminium:	50 µm
Thickness of adhesive:	1 150 µm
Total tape thickness:	1 200 µm
Adhesion:	2,0 N/mm min
(Metal, plastics, primed concrete and self)	

Surface Preparation:

Ensure that surfaces are dry, in sound condition, clean and free from any contaminants such as dust, dirt, rust, salt, algae and grease. Remove all loose materials mechanically, then thoroughly clean surfaces with a suitable surface cleaner. Metal surfaces must be free of rust. Allow **SCC Bit-U-Tape** to warm up in the sun before proceeding with application.

Bonding/ Priming:

Prime surfaces with **GB15 GripBond**. Allow **GB15 GripBond** to dry fully before proceeding with **SCC Bit-U-Tape** application.

Application:

Cut **SCC Bit-U-Tape** to size before removing paper wrapping. Once desired lengths have been cut, apply **SCC Bit-U-Tape** to the required area.

Sealing: overlaps must be a minimum of 50 mm as flashing between a wall and a corrugated roof. Any gaps must be filled with a chosen mortar from the **SCC GripRepair** range.

SCC Bit-U-Tape is to be left with the aluminium protective layer as is after application.

Limitations:

- Application temperature range: + 5° C - + 40° C
- **SCC Bit-U-Tape** must not be applied in freezing, wet or foggy conditions.

Packaging:

Available in the following sizes (W x L):

50mm x 2.5m

75mm x 10m

100mm x 10m

150mm x 10m

Storage and Shelf Life:

Store in a cool, dry place in original packaging. This product will have a shelf life of 12 months when stored appropriately.

Health and Safety Information:



Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. For further health and safety information refer to the product SDS.

Stanton Construction Chemicals Pty (Ltd).

Unit 2A Veni View Park 547 Heritage View Drive
Muldersdrift, South Africa, 1735

Tel: +27 (0) 10 593-4454

Email: www.office.co.za

Website: www.sccsa.co.za



The information, and, in particular, the recommendations relating to the application and end-use of SCC products, are given in good faith based on SCC's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with SCC's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. SCC reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. Users must always refer to the most recent issue of the Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of SCC