

Product Description

Film faced plywood is quality plywood panel produced predominantly from graded Pinus radiata veneers. These are glued with phenol formaldehyde resin and overlaid with a hard durable resin impregnated paper to give concrete a smooth finish. The hard phenolic surface and high quality outer veneers make it durable and reusable. Ideal for general formwork use such as decks, retaining walls, bridges and culvert construction.

Specifications Product Name: Film faced plywood

Sheet size: 1220x2440mm, 1250x2500mm, 2400x1200mm & 1800x1200mm , or as request.

Thickness: 9mm~21mm

Core: Poplar, hardwood or combi, etc.

Film: Black, Brown, Red or Anti-slipe film

Glue: Melamine, WBP Phenolic

Recycle used: 3~4 times, 6 ~8 times, above 10 times.

Edge: Edges sealed with waterproof print (color is optional)

Specification

Product name	Film Faced Plywood
Brand	LEBERG
Size	1220x2440mm, 1250x2500mm or custom
Thickness	9-25mm or upon request
Core	Combi core, poplar core, eucalyptus core, birch core, finger Joint etc.
Density	550-700 kg/m ³ (+/- 50 kg)
Glue	MR, Melamine, WBP
Thickness tolerance	+/-0.5mm
Moisture Content	10% (+/- 2%)
Modulus of rupture	≥30Mpa
Modulus of Elasticity	≥6000Mpa
Certification	CE ISO9001 CARB
Usages	Construction
Delivery time	Within 15 days after receiving deposit or original L/C at sight,Urgent orders to be negotiated
Customized	OEM/ODM both are available.

Grupo Easy, Lda

Av. das Estâncias nº 344 Armazém 5 – Maputo, Moçambique

c.: (+258) 852929290 | e.: geral@easy.co.mz

www.easy.co.mz







PLYWOOD FORMWORK

1220mm x 2440mm x 18mm

Grupo Easy, Lda

Av. das Estâncias nº 344 Armazém 5 – Maputo, Moçambique
c.: (+258) 852929290 | e.: geral@easy.co.mz

www.easy.co.mz

